

Vintessential Laboratories	Chemwatch Hazard Alert Code: 2
Chemwatch: 52-9775	Issue Date: 08/17/2015
Version No: 2.1.1.1	Print Date: 12/21/2016
Safety Data Sheet according to WHS and ADG requirements	

# SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### **Product Identifier**

Product name	Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH (Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH)	
Synonyms	Not Available	
Other means of identification	Not Available	

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General laboratory reagent. Measuring ammonia in grape juice and wine.

# Details of the supplier of the safety data sheet

Registered company name	Vintessential Laboratories	
Address	32 BRASSER AVENUE DROMANA VIC 3936 Australia	
Telephone	+61 3 5987 2242	
Fax	+61 3 5987 3303	
Website	Not Available	
Email	Not Available	

# **Emergency telephone number**

Association / Organisation	Not Available
Emergency telephone numbers	+61 405 318 590
Other emergency telephone numbers	Not Available

# **SECTION 2 HAZARDS IDENTIFICATION**

### Classification of the substance or mixture

Poisons Schedule	Not Applicable	
Classification <sup>[1]</sup>	Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation)	



# Precautionary statement(s) Response

P362	Take off contaminated clothing and wash before reuse.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER or doctor/physician if you feel unwell.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P302+P352	IF ON SKIN: Wash with plenty of soap and water.	
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.	
P332+P313	If skin irritation occurs: Get medical advice/attention.	

# Precautionary statement(s) Storage

P405	Store locked up.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

### Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.
------	---

# SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

### Substances

See section below for composition of Mixtures

### **Mixtures**

CAS No	%[weight]	Name
56-81-5	30-60	glycerol
10049-21-5	1-10	sodium phosphate, monobasic, monohydrate
7558-79-4	1-10	sodium phosphate, dibasic
	balance	Ingredients determined not to be hazardous

# **SECTION 4 FIRST AID MEASURES**

# Description of first aid measures

Eye Contact

- If this product comes in contact with the eyes: Wash out immediately with fresh running water.
- + Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally

Print Date: 12/21/2010 Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH (Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH)		
	<ul> <li>lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>	
Skin Contact	<ul> <li>If skin contact occurs:</li> <li>Immediately remove all contaminated clothing, including footwear.</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>	
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> </ul>	
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>	

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5 FIREFIGHTING MEASURES**

### Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

In foam.

- dry chemical powder.
- carbon dioxide.

# Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.		
Advice for firefighters			
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> <li>DO NOT approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> <li>Equipment should be thoroughly decontaminated after use.</li> </ul>		
Fire/Explosion Hazard	<ul> <li>The material is not readily combustible under normal conditions.</li> <li>However, it will break down under fire conditions and the organic component may burn.</li> <li>Not considered to be a significant fire risk.</li> <li>Heat may cause expansion or decomposition with violent rupture of containers.</li> <li>Decomposes on heating and may produce toxic fumes of carbon monoxide (CO).</li> <li>May emit acrid smoke.</li> </ul> Decomposes on heating and produces toxic fumes of: <ul> <li>carbon dioxide (CO2)</li> <li>hydrogen cyanide</li> <li>acrolein</li> <li>nitrogen oxides (NOx)</li> <li>other pyrolysis products typical of burning organic material.</li> </ul>		
HAZCHEM	Not Applicable		

# SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

# **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Slippery when spilt.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>Wipe up.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>
Major Spills	<ul> <li>Slippery when spilt.</li> <li>Moderate hazard.</li> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Stop leak if safe to do so.</li> <li>Contain spill with sand, earth or vermiculite.</li> <li>Collect recoverable product into labelled containers for recycling.</li> <li>Neutralise/decontaminate residue (see Section 13 for specific agent).</li> <li>Collect solid residues and seal in labelled drums for disposal.</li> <li>Wash area and prevent runoff into drains.</li> <li>After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>If contamination of drains or waterways occurs, advise emergency services.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# SECTION 7 HANDLING AND STORAGE

# Precautions for safe handling

Safe handling	<ul> <li>DO NOT allow clothing wet with material to stay in contact with skin</li> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> <li>DO NOT enter confined spaces until atmosphere has been checked.</li> <li>DO NOT allow material to contact humans, exposed food or food utensils.</li> <li>Avoid contact with incompatible materials.</li> <li>When handling, DO NOT eat, drink or smoke.</li> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with soap and water after handling.</li> <li>Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> <li>Protect containers against physical damage and check regularly for leaks.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

# Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Polyethylene or polypropylene container.</li> <li>Packing as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	Avoid reaction with oxidising agents

# SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

# OCCUPATIONAL EXPOSURE LIMITS (OEL)

# INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	glycerol	Glycerin mist	10 mg/m3	Not Available	Not Available	Not Available

# EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
glycerol	Glycerine (mist); (Glycerol; Glycerin)	45 mg/m3	860 mg/m3	2,500 mg/m3
sodium phosphate, monobasic, monohydrate	Sodium phosphate monobasic monohydrate	30 mg/m3	330 mg/m3	2,000 mg/m3
Ingredient	Original IDLH	Revised IDLH		
glycerol	Not Available	Not Available		
sodium phosphate, monobasic, monohydrate	Not Available	Not Available		
sodium phosphate, dibasic	Not Available	Not Available		

#### MATERIAL DATA

CEL Ceiling: 0.00006 mg/m3 (sensitiser)

(compare TLV-C subtilisins; proteolytic enzymes - 100% crystalline)

Exposure at or below the recommended TLV-C is thought to minimise the potential for allergic respiratory sensitization for the majority of immunologically normal persons and to minimise skin irritation and sensitization. TLV compliance is contingent on measurement of workplace air concentrations with a high volume sampler appropriate to capture these proteins for at least 60 minutes.

Although the recommended TLV-C is specifically prescribed for subtilisins, the Chemwatch recommendation (CEL) recognizes that all proteins have the potential to produce allergic responses. It should be noted, however, that proteins are typically poorly absorbed through the skin and after inhalation. Literature reports indicate that protein bioavailability, via the lung, is as low as 2%.

### Exposure controls

	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. Provide adequate ventilation in warehouses and enclosed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.			
Appropriate	Type of Contaminant:		Air Speed:	
engineering controls	solvent, vapours, degreasing etc., evaporating from tank (in still air).		0.25-0.5 m/s (50-100 f/min)	
	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)		0.5-1 m/s (100-200 f/min.)	
	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)		1-2.5 m/s (200-500 f/min.)	
	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion)		2.5-10 m/s (500-2000 f/min.)	
	Within each range the appropriate value depends on:			
	Lower end of the range Upper end of the range			
	1: Room air currents minimal or favourable to capture	e 1: Disturbing room air cu		

2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

	systems are installed of used.
Personal protection	
Eye and face protection	<ul> <li>Safety glasses with side shields.</li> <li>Chemical goggles.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>
Skin protection	
Hands/feet protection	<ul> <li>Wear chemical protective gloves, e.g. PVC.</li> <li>Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>NOTE: <ul> <li>The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> <li>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</li> <li>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</li> <li>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.</li> <li>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: <ul> <li>frequency and duration of contact,</li> <li>destrity</li> </ul> </li> <li>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</li> <li>When only brief contact is expected, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>Some glove polymer types are less affected by movement and this should be taken into account when considering gloves should be replaced.</li> <li>Contaminated gloves should be replaced.</li> </ul> </li> <li>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</li> <li>Some gl</li></ul>
	<ul> <li>task.</li> <li>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: <ul> <li>Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> </li> <li>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</li> </ul>

Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>P.V.C. apron.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> <li>Eye wash unit.</li> </ul>
Thermal hazards	Not Available

### Recommended material(s)

### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH (Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH)

Material	CPI
NATURAL RUBBER	В

\* CPI - Chemwatch Performance Index

### A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion **NOTE**: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

### Respiratory protection

# Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

#### ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance	Clear liquid; miscible with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	7.0	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available

Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# SECTION 11 TOXICOLOGICAL INFORMATION

### Information on toxicological effects

Inhaled	Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.
Skin Contact	<ul> <li>The material may accentuate any pre-existing dermatitis condition</li> <li>Open cuts, abraded or irritated skin should not be exposed to this material</li> <li>The material produces mild skin irritation; evidence exists, or practical experience predicts, that the material either</li> <li>produces mild inflammation of the skin in a substantial number of individuals following direct contact, and/or</li> <li>produces significant, but mild, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.</li> <li>Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.</li> </ul>
Eye	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals. Repeated or prolonged eye contact may cause inflammation (similar to windburn) characterised by a temporary redness of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.
Chronic	Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. Limited evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a significant number of individuals at a greater frequency than would be expected from the response of a normal population. Pulmonary sensitisation, resulting in hyperactive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching. Significant symptoms of exposure may persist for extended periods, even after exposure ceases. Symptoms can be activated by a variety of nonspecific environmental stimuli such as automobile exhaust, perfumes and passive smoking.

TOXICITY

dermal (rat) LD50: >2000 mg/kg<sup>[1]</sup>

Oral (rat) LD50: 7.4 gm<sup>[1]</sup>

sodium phosphate,

Ammonia analysis kit

for Discrete

dibasic

Chemwatch: 52-9775	Page <b>9</b> of <b>1</b>	3	Issue Date: 08/17/2015
/ersion No: 2.1.1.1 Vin	tessential Ammonia analysis kit for Discrete Au Ammonia analysis kit for Discrete Au	toanalysers, Reagent 3, GIDH (Vintessential itoanalysers, Reagent 3, GIDH)	Print Date: 12/21/2016
	There exists limited evidence that shows that skin correaction in a significant number of individuals, and/or There is a possibility that unintended contact with the membrane, or inhalation) could result in allergic or repeated exposures or in persons with a pre-existing Dusts produced by proteins are capable, under certa foreign proteins. Typical allergic asthma may be rap sputum production, fever, myalgia, fatigue, airway of pattern, or basal or apical fibrosis. In addition there is severe dyspnoea may develop giving a clinical pictuallergic alveolitis. No irritation is likely after brief ski in soreness, redness, inflammation and possible ulco of lung function due to fibrotic change.	ontact with the material is capable either of inducing a set of producing positive response in experimental animals this product (such as through a cut, needle stick, eye or hypersensitivity reactions. Such reactions are more likely allergy to certain proteins. ain conditions, of sensitising workers by virtue of the bod bidly produced after exposure, with symptoms may includ bstruction; chest radiographs may show a generalised re may be retrosternal discomfort, headache, stomach-ache ure similar to that of farmer's lung and allied conditions of n contact, but prolonged contact in the presence of mois eration of the skin. Repeated attacks may lead to perma	nsitisation mucous y following lies reaction to le chronic cough, ticulonodular e and general f extrinsic sture may result nent impairment
Vintessential Ammon analysis kit fo Discre	ia or te		
Reagent 3, GID		IRRITATION	
(Vintessenti Ammonia analysis k for Discre Autoanalyser Reagent 3, GID	al Not Available it s, H)	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
glycer	dermal (guinea pig) LD50: 54000 mg/kg <sup>[1]</sup>	Not Available	
5,744	Oral (rat) LD50: >20-<39800 mg/kg <sup>[1]</sup>		
sodium nhosphat	тохісіту	IRRITATION	
monobasi	c, Oral (rat) LD50: 8290 mg/kg <sup>[2]</sup>	Eye (human): 50 mg - mild	
monohydra	te	Eve (rebbit): 150 mg mild	

Eye (rabbit): 150 mg - mild

Eye (rabbit): 500 mg/24h - mild

Skin (rabbit): 500 mg/24h - mild

IRRITATION

Legend:	<ol> <li>Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances</li> </ol>
Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH (Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH)	No significant acute toxicological data identified in literature search.
SODIUM PHOSPHATE, MONOBASIC, MONOHYDRATE	Data for anhydride
SODIUM PHOSPHATE, DIBASIC	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.
Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH (Vintessential	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe

bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation

Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH (Vintessential
Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH)

Autoanalysers, Reagent 3, GIDH) & GLYCEROL & SODIUM PHOSPHATE, MONOBASIC, MONOHYDRATE & SODIUM PHOSPHATE, DIBASIC	is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.		
Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH (Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH) & GLYCEROL	For glycerol: Acute toxicity: Glycerol is of a low order of acute oral and very high dose levels, the signs of toxicity include tremor a irritation studies indicate that glycerol has low potential to irri- together with the very widespread potential for exposure an glycerol is not a skin sensitiser. <b>Repeat dose toxicity:</b> Repeated oral exposure to glycerol gastro-intestinal tract. The overall NOEL after prolonged tre dose level no systemic or local effects were observed. For effects to the upper respiratory tract is 165 mg/m3 and 66 <b>Genotoxicity:</b> Glycerol is free from structural alerts, which mutations in bacterial strains, chromosomal effects in mam gene mutation test in mammalian cells were of uncertain bid significant effect in a chromosome aberrations and dominar absence of a positive control, prevent any reliable conclusive considered to possess genotoxic potential. <b>Carcinogenicity:</b> The experimental data from a limited 2 y concerns in relation to carcinogenicity. Data from non-guide male mice suggest that oral administration of glycerol up to tumour formation. <b>Reproductive and developmental toxicity:</b> No effects on generation study with glycerol administered by gavage (NO effects were seen in the rat, mouse or rabbit at the highest (NOEL 1180 mg/kg bw/day).	dermal toxicity wi nd hyperaemia of ritate the skin and d the absence of does not induce a atment with glyce inhalation exposu 2 mg/m3 for syste raise concern for malian cells or pro logical relevance nt lethal study. Ho ons to be drawn fi ear dietary study line studies desig 20 weeks had a fertility and repro AEL 2000 mg/kg dose levels tested	th LD50 values in excess of 4000 mg/kg bw. At if the gastro-intestinal -tract. Skin and eye the eye. The available human and animal data, case reports of sensitisation, indicate that adverse effects other than local irritation of the rol is 10,000 mg/kg bw/day (20% in diet). At this irre to aerosols, the NOAEC for local irritant emic effects. mutagenicity. Glycerol does not induce gene imary DNA damage <i>in vitro</i> . Results of a limited . <i>In vivo</i> , glycerol produced no statistically owever, the limited details provided and the rom the <i>in vivo</i> data. Overall, glycerol is not in the rat does not provide any basis for med to investigate tumour promotion activity in weak promotion effect on the incidence of oductive performance were observed in a two bw/day). No maternal toxicity or teratogenic d in a guideline comparable teratogenicity study
Acute Toxicity	© c	arcinogenicity	0
Skin Irritation/Corrosion	✓	Reproductivity	0
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	*
Respiratory or Skin sensitisation	S	FOT - Repeated Exposure	0
Mutagenicity	⊗ Asp	iration Hazard	0

Legend: X – Data available but does not fill the criteria for classification

Data required to make classification available

# $\bigcirc$ – Data Not Available to make classification

# **SECTION 12 ECOLOGICAL INFORMATION**

Toxicity					
Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
glycerol	LC50	96	Fish	>11mg/L	2
glycerol	EC50	96	Algae or other aquatic plants	77712.039mg/L	3
glycerol	EC0	24	Crustacea	>500mg/L	1
sodium phosphate, monobasic, monohydrate	LC50	96	Fish	186mg/L	4
Legend:	Extracted from 1. IL 3. EPIWIN Suite V3 Aquatic Hazard Ass Data	JCLID Toxicity Data 2. Euro 3.12 - Aquatic Toxicity Data sessment Data 6. NITE (Jap	pe ECHA Registered Substances - (Estimated) 4. US EPA, Ecotox dat an) - Bioconcentration Data 7. MET	Ecotoxicological Information - abase - Aquatic Toxicity Data TI (Japan) - Bioconcentration E	Aquatic Toxicity 5. ECETOC Data 8. Vendor

For glycerol log Kow : -2.66- -2.47 BOD 5: 0.617-0.87,31-51% COD: 1.16,82-95% ThOD: 1.217-1.56 Completely biodegradable.

# Continued...

Version No: 2.1.1.1

# Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH (Vintessential Ammonia analysis kit for Discrete Autoanalysers, Reagent 3, GIDH)

### Environmental fate:

Based on the relevant physical-chemical properties and the fact that glycerol is readily biodegradable, glycerol will partition primarily to water. Biodegradability: Glycerol is considered to be readily biodegradable in the aquatic environment. Pre-adapted microorganisms can degrade glycerol rapidly under both aerobic and anaerobic conditions.

Bioaccumulation: Based on Log Kow -1.76, glycerol will have a low bioaccumulation potential and is not expected to bioaccumulate.

Photodegradation: The calculated half-life for the photo-oxidation (reaction with hydroxyl radicals) of glycerol in air is 6.8 hours (EPIWIN vs 3.04). Stability in Water: Glycerol does not contain functional groups that are expected to react with water.

Transport between Environmental Compartments: From the EQC model (Mackay level III), it can be deduced that 100% of glycerol will end up in the water phase. Negligible amounts will be distributed towards soil, air and sediment

Ecotoxicity:

Fish LC50: >5000 mg/l

Algae IC50: >2900 mg/l

Bacteria EC50: .10000 mg/l (Pseudomonas putida)

The weight of evidence indicates that glycerol is of low toxicity to aquatic organisms and this conclusion is supported by QSAR predictions. The lowest LC50 for fish is a 24-h LC50 of >5000 mg/l for Carassius auratus (Goldfish) and for aquatic invertebrates, a 24 h EC50 of >10000 mg/l for Daphnia magna is the lowest EC50. Several tests on algae are available, which suggest very low toxicity to a range of species, however their validity is uncertain. A QSAR prediction for the 96h EC50 to algae was 78000 mg/l. No toxicity towards the microorganism Pseudomonas putida was observed at 10000 mg/l after exposure for 16 hours. No long-term aquatic toxicity data is available. Screening studies are available on frog and carp embryos which indicate some effects on growth and hatching rates respectively at very high concentrations of glycerol, >7000 mg/l. However, their ecological relevance is not clear.

### Proteins are generally easily biodegradable.

DO NOT discharge into sewer or waterways.

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
glycerol	LOW	LOW

### **Bioaccumulative potential**

Ingredient	Bioaccumulation
glycerol	LOW (LogKOW = -1.76)

### Mobility in soil

Ingredient	Mobility
glycerol	HIGH (KOC = 1)

### SECTION 13 DISPOSAL CONSIDERATIONS

### Waste treatment methods

### Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

# Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

### Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

### Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

### Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Australia Exposure Standards

### SECTION 15 REGULATORY INFORMATION

### Safety, health and environmental regulations / legislation specific for the substance or mixture

GLYCEROL(56-81-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

# SODIUM PHOSPHATE, MONOBASIC, MONOHYDRATE(10049-21-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

### SODIUM PHOSPHATE, DIBASIC(7558-79-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (glycerol; sodium phosphate, monobasic, monohydrate; sodium phosphate, dibasic)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

### **SECTION 16 OTHER INFORMATION**

### Other information

### Ingredients with multiple cas numbers

Name	CAS No
glycerol	56-81-5, 29796-42-7, 30049-52-6, 37228-54-9, 75398-78-6, 78630-16-7, 8013-25-0
sodium phosphate, dibasic	7558-79-4, 10028-24-7

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### **Definitions and abbreviations**

- PC-TWA: Permissible Concentration-Time Weighted Average
- PC-STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit。
- IDLH: Immediately Dangerous to Life or Health Concentrations
- OSF: Odour Safety Factor
- NOAEL :No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value BCF: BioConcentration Factors
- BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.